



EQUIPMENT CATALOGUE



The best seeds deserve the best, most high-powered equipment, so we equipped ourselves with top-of-the-line seeding machinery.



HS-900 X3

900 GAL

The HS-900 X3 is among the top units of its kind. It has a tank capacity of 900 GAL and a 22KW Kohler engine that gives an additional 4-meter discharge distance. This was originally designed for rugged use within Southeast Asia, thus primed for years of reliable performance and service.

EQUIPMENT SPECS:

- **Power**
30 HP (22 KW) Kohler
- **Discharge**
Positive displacement gear pump
- **Agitation**
Mechanical paddle
- **Drive Lubrication**
Mobile | Synthetic 75 W-90 non-foaming
- **Fuel**
6.6 gallons unleaded gasoline
- **Tank capacity**
P900 gallons (3,407 L)
- **Mulch capacity**
450 – 675 lbs. (205 – 306 kg)
- **Wheat straw mulch coverage per load**
11,750 – 14,700 sq ft (1090 – 1365 sqm)
- **Wood/Paper mulch coverage per load**
9,800 sq ft (900 sqm)
- **Discharge distance**
Up to 90 ft (27 m)
- **Set of 3 nozzles**
1 medium fan spray, 1 distance spray, 1 wide fan
- **Skid L x W x H**
150 x 51 x 96 in (381 x 129.5 x 243.8 cm)
- **Trailer L x W x H**
187 x 78 x 126 in (475 x 1981 x 320 cm)
- **Skid empty weight**
2,800 lbs. (1,270 kg)
- **Skid loaded weight**
9,500 lbs. (4,309 kg)
- **Trailer empty weight**
3,200 lbs. (1,451 kg)
- **Trailer loaded weight**
9,900 (4,491 kg)



HS-83K

2000 GAL

The HS-83K has an 83KW diesel engine with a tank capacity of 2000 GAL. With its power, performance, and production, this seeder is the economical choice for various areas, including commercial properties, highway roadsides, industrial parks, sports fields, and mining sites.

EQUIPMENT SPECS:

- **Power**
83KW
- **Tank effective capacity**
8,000L
- **Output pressure**
1.05MPa
- **Output**
90m³/h
- **Maximum aggregate**
10mm
- **Rotating speed**
2400rpm
- **Maximum horizontal conveying distance**
70m
- **Height of fence**
850mm
- **Dimensions**
5000x2100x2600mm
- **Weight**
3700kg



HS-8 X3

SEDIMENT AND EROSION CONTROL

It's a low-cost and high-efficiency equipment for filling Soxx. It has a universal skid steer mount, a two yard capacity hopper, and a hydraulically power auger.

The HS-8 is a diverse unit. It can either be used as a production unit at your warehousing facilities, producing SiltSoxx stocks ready for when that next big project comes in.

Alternatively, having a universal skid steer mount it can be used to produce SiltSoxx onsite directly in place if needed. This can be a really efficient way of installing your SiltSoxx. With few restrictions on the filling material, this can reduce logistic costs considerably. Using debris materials from site and producing the SiltSoxx where they're needed.

EQUIPMENT SPECS:

- **Hydraulic Motor**
Eaton 6000 Series Power Source
- **Weight**
1,200 lbs. (544 kg)
- **Max Capacity**
2,000 lbs. (907 kg)
- **Dimensions**
54"H x 139"L x 69"W (137 H x 353 L x 175 W cm)



 greenacres.com.ph

 solutions@greenacres.com.ph

 (+632) 8645 9040

 7th floor, SMB Prestige bldg. 40 San Buenaventura St.,
Bagong Ilog, Pasig City